



DEKOFFLASH ONE (3mm)

装饰型环氧自流平系统 DECORATIVE EPOXY SELF-LEVELLING SYSTEM

DEKOFFLASH ONE (3mm) 是由三组份无溶剂环氧自流平及不同尺寸的球状石英砂组成的系统, 可以施工成平整无缝的装饰地坪, 适用于住宅 / 商业项目。DEKOFFLASH ONE 系统平整度非常高, 耐磨及耐化学品性能极佳, 防水, 容易清洁, 同时还是风格、纯粹、优雅的代名词, 通过不同的树脂色彩可以营造出不同的情感氛围。

DEKOFFLASH ONE (3mm) is a three-component self-levelling solvent-free epoxy system with size-graded ball-shaped quartz that has been specifically designed to provide uninterrupted decorative floorings with a monochrome effect in residential / commercial applications. DEKOFFLASH ONE displays very high performances (perfectly flat, resistant to wear and chemical aggression, waterproof and easy to clean) and is at the same time a synonym for style, purity and elegance, with the color of the resin taking on the task of creating emotion.

适用场所 Applications

- > 公寓 Apartments
- > 别墅 Houses
- > 商店 Shops
- > 展厅 Showrooms
- > 办公室 Offices
- > 会议场所 Conference halls
- > 宾馆 Hotels
- > 餐厅及酒吧 Restaurants and bars

平整无缝
Flat and seamless

美观
Aesthetic

易施工
Easy to apply

良好的耐化学品性能和机械性能
Good chemical resistance
& Good mechanical properties

技术标准 Technical standard	
交通载荷 Traffic load	轻 / 中度 Light / medium
施工温度 Application temperature	+10°C~30°C
防火等级 Reaction to fire	B _n -s1
腐蚀性物质的释放 Release of corrosive substances	SR
耐磨性 Wear resistance	< AR1
粘结强度 Bond strength	> B1.5
耐冲击性 Impact resistance	≥ IR10



步骤 Step	产品 Product	说明 Information	理论用量 Consumption	施工方法 Application method	覆涂间隔时间 Overcoating
基面 Substrate	处理 Preparation	机械处理, 清洁 Mechanical treatment and cleaning of base	—	—	—
底涂 Primer	PRIMER MU + MICROFILLER R in a 1:1~2 ratio	无溶剂环氧底涂+填充料 Solvent-free epoxy resin primer with added filler	0.7kg/m ²	滚涂 Roller	8小时后 Allow 8 hours
撒播 Broadcast	石英砂 QUARTZ 0.1-0.5	在刚施工好的底涂上播撒石英砂 Broadcast of quartz on the freshly-applied primer	3.0kg/m ²	用手播撒 Scatter by hand	
自流平 Self-levelling	FLOORPOX + QUARTZ AV in a 1.5:1.4 ratio	无溶剂环氧自流平 Self-levelling solvent-free epoxy resin coating	4.0kg/m ²	镬涂 Trowel	8小时后 Allow 8 hours
面涂 Finish	KEMCOGLASS PU1	透明的无溶剂脂肪族聚氨酯 Transparent solvent-free aliphatic polyurethane resin	0.1kg/m ²	滚涂 Roller	—

